Model		Accuracy	Diameter Range	Application				
Laser Levels								
LL100N		1/8 in @ 100 ft (3.0 mm @ 30 m)	1,150 ft (350 m)	Forms, footings and foundations (residential jobs) Septic tank or swimming pool installations Estimating cut and fill Decks and terraces				
LL300N		3/32 in @ 100 ft (2.2 mm @ 30 m)	1,650 ft (500 m)	 Elevation control across small- and mid-size construction sites Excavations Basic slopes Leveling forms and footers Concrete pours 1 m (4 ft) marks 				
LL300S		1/16 in @ 100 ft (1.5 mm @ 30 m)	2,600 ft (800 m)	General elevation control Checking and setting elevations for small to medium job sites Leveling forms and footers Estimating cut and fills Excavations Basic slopes for driveways and ramps				
LL400HV		1/16 in @ 100 ft (1.5 mm @ 30 m)	2,600 ft (800 m)	Checking/setting elevations, concrete forms, footings, and foundations for large commercial jobs Basic slope work such as foundations for small-to-large site prep work Excavating for forms or footers with CR600 receiver Sub-base leveling with skid steer loaders and CR600 receiver				
LL500	The same of the sa	1/16 in @ 100 ft (1.5 mm @ 30 m)	1,600 ft (500 m)	 Checking elevations Setting concrete forms, footings, and foundations (small-to-large jobs) Ideal for larger pads Machine control compatible 				
			Grade & Universa	al Lasers				
GL412N/ GL422N		1/16 in @ 100 ft (1.5 mm @ 30 m)	2600 ft (800 m)	 Leveling concrete forms and footers Vertical alignment and plumb such as anchor bolt and form alignment Single and dual slope grading and excavating applications Grading Parking lots, tennis courts and driveways 				
GL612/ GL622		1/16 in @ 100 ft (1.5 mm @ 30 m)	2600 ft (800 m)	 Steep slope road embankments and ditch banks High accuracy grade work Wireless remote monitoring with HL750 Single and dual slope grading and excavating applications 				
UL633		1/16 in @ 100 ft (1.5 mm @ 30 m)	2600 ft (800 m)	 Dual slope grading and steep slope excavating Precision grade up to 25% in X, Y and Z axis Drift free vertical alignment and plumb Measuring slopes in open trenches and existing pipes 				
GL710/ GL720/ GL722		1/32 in @ 100 ft (0.8 mm @ 30 m)	3000 ft (900 m)	High accuracy grade work Single and dual slope grading and excavating applications Machine control compatible General construction site preparation and road construction				

General construction, site preparation and road construction

Laser Levels						Grade & Universal Lasers		
	LL100N	LL300N	LL300S	LL400HV	LL500	GL412N/422N	GL612/622	UL633
Laser type / classification	650 nm, Class 2	650 nm, Class 2	650 nm, Class 2	650 nm, Class 2	670 nm, Class 2	650 nm, Class 2	650 nm, Class 2/ 3 mW	650 nm, Class 3A/3R, <5mW
Self-leveling range	±5 degrees electronic servo self-leveling	±5 degrees electronic servo self-leveling	±5 degrees electronic servo self-leveling	±5 degrees electronic servo self-leveling	±11 minutes wire hung compensator	±5 degrees electronic servo self-leveling	±14 degrees electronic servo self-leveling	±14 degrees electronic servo self- leveling
Out-of-level indication	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Power source	2 x D-cell Alkaline	4 × D-cell Alkaline standard, recharge optional	4 × D-cell Alkaline standard, recharge optional	4 x D-cell Alkaline standard, NiMH optional	4 × D-cell Alkaline standard, recharge optional	4 x D-cell NiMH standard, Alkaline backup	4 x D Cell, NiMH Pack standard, Alkaline backup	4 x D Cell, NiMH Pack standard, Alkaline backup
Battery life	80 hr Alkaline	90 hr Alkaline, 45 hr NiMH	60 hr Alkaline, 47 hr NiMH	60 hr Alkaline, 47 hr NiMH	175 hr Alkaline, 100 hr NiMH	50 hr Alkaline, 35 hr NiMH	40 hr alkaline, 35 hr NiMH	40 hr alkaline, 35 hr NiMH
Grade Capability	Manual - Single axis	Manual - Single axis	Manual - Single axis	Manual - Dual Axes	No	Electronic -10 to +15% Single Axis/ Dual Axes	Electronic -25% to +25% Single Axis/ Dual Axes	Electronic -25% to +25% X, Y, Z Axis
Warranty	3 Years Limited	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years

Optical Auto Levels / Theodolites									
	AL20M	AL24A	AL24M	AL28M / AL28M-G	AL32A	DET-2			
Magnification	20x	24×	24×	28×	32x	30x			
Accuracy	+/- 2.5 mm (0.10 in)*	±2.0 mm (0.08 in)*	±2.0 mm (0.08 in)*	±1.5 mm (0.06 in)*	±1.0 mm (0.04 in)*	±50 mm (2 in)			
Aperture	30 mm (1.2 in)	30 mm (1.2 in)	30 mm (1.2 in)	30 mm (1.2 in)	36 mm (1.4 in.)	45 mm (1.8 in.)			
Shortest focus	0.6 m (1.97 ft)	0.6 m (1.97 ft)	0.6 m (1.97 ft)	0.6 m (1.97 ft)	0.6 m (1.97 ft)	1.45 m (4.76 ft)			
Compensator	Magnetic dampened	Air dampened	Magnetic dampened	Magnetic dampened	Air dampened	Automatic			
				AL28M-G available in gon					

^{*}Note: Standard deviation according to DIN 18723 on one kilometer of double leveling

THE BROADEST LINE FROM THE STRONGEST NAME IN LASERS



An Entire industry. Invented here.

There's a reason Spectra Precision is the strongest name in the industry. We invented the industry. From day one, we have pioneered every major development in laser positioning for construction. That's why you'll find over one million of our professional rotating lasers on job sites around the world... more than any other brand.

Easiest to Use

Spectra Precision instruments are engineered with state-ofthe-art components, giving you the most dependable, easiest to use, laser on the job site. Spectra Precision products are always ready to work when you are.

Best Support

Each Spectra Precision product is built with the user in mind. That is why we test and retest every laser we manufacture to assure you the most dependable, accurate laser in the world. Backed by the world's largest network of repair centers, Spectra Precision is unmatched for service, support and dependability.

YOUR LOCAL SPECTRA PRECISION LASER DEALER

Contact Information:

TRIMBLE / SPECTRA PRECISION DIVISION

5475 Kellenburger Road Dayton, Ohio 45424 U.S.A. (888) 527-3771 (Toll Free in U.S.A.) +1-937-245-5600 Phone

+1-937-245-5489 Fax www.spectralasers.com

EUROPE

Trimble Kaiserslautern GmbH Am Sportplatz 5 67661 Kaiserslautern GFRMANY Tel +49-(0)6301-71 14 14 Fax +49-06301-32213



© 2015, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and Spectra Precision are trademarks of Trimble Navigation Limited registered in the United States Patent and Trademark Office and other countries. All other trademarks are the property of their respective owners. PN 022507-406 (01/15)



PRODUCTIVITY TOOLS

2015 CONSTRUCTION





Toughest on Earth **Strongest Warranty** Easiest to Use

LL100N

Complete system in one case includes laser, HR320 receiver, rod. and tripod

Convenient storage and transportation.

Compensated self-leveling. maintains level automatically

 Maintains accuracy over the entire work area, and minimizes errors.

Robust design

 3 year no downtime warranty keeps productivity high and operating costs low.



11300N

New standard in ruggedness

Superior drop and weather protection.

Fully automatic self-leveling

Provides fast and accurate set-up.

Single axis manual slope mode via optional RC601 remote control

 RC601 makes slope matching to a single person operation.



LL300S

Highly durable construction

Superior drop and weather protection.

Fully automatic self-leveling

Provides fast and accurate set-up.

Extremely versatile with single-axis manual slope

 Cross-axis self-leveling allows for grade matching on the job site.





11400HV

Fast setup and automatic H + V self-leveling

 Minimizes operating costs and boosts productivity.

Highly durable construction

Superior drop and weather protection.

Single-axis slope mode selectable on both axes

 Provides grade matching with self-leveling cross axis.



500 m (1.600 ft) working diameter

 Long-range accurate laser increases productivity by reducing the need for multiple setups on large job sites.

Built-in leveling system with out-of-level shut off

 Maintains accuracy over the entire work area and minimizes errors.

High accuracy laser, 1.5 mm per 30 m (1/16 per 100 ft) with temperature compensation

 Highly stable and repeatable accuracy even under large temperature changes



GRADE LASERS

GL412N/GL422N

Fully automatic self-leveling performs three iobs cost effectively

■ Level. -10 to +15% grade, and vertical alignment with plumb.

Full function remote control does everything you can do at the laser keypad

 Make grade changes from anywhere on the job reducing setup times.

Menu driven user interface

 Reduces learning time and eliminates complex button pressing.

GL612/GL622

Ultimate Control of X/Y Axes

■ Fully automatic up to +/-25% grade

Wireless communication with the **HL750** Laserometer

- Grade Matching easily measure
- PlaneLok locks the beam to a fixed elevation or vertical alignment point for maximum stability and accuracy.

2-way full function radio remote

Perform all functions at the laser







DigiRod DR400

The Rod-less Grade Checker

Tilt Sensor - All-in-One.

Digital Readout receiver, Distance Meter,

GL710. GL720. GL722

Single & Dual Grade Lasers

-0,5 to +25% grade range on the Y-axis and \pm 10% on the X-axis (GL720, GL722) with high accuracy.

Active temperature compensation Accurate, stable results regardless of

temperature changes.

Large Alpha/Numeric Display for each axis

 Transmitter displays are visible from ground even used on tall 10 ft (3 m) tripods.

- Automatic Axis Alignment.

UL633

The most versatile laser ever

UNIVERSAL LASERS

 Dual Grade, Horizontal. Vertical, Interior and Layout Laser based on Fanbeam technology.

Fully automatic +/-25% in X. Y and Z axis

 Total control for any application.

Several unique advanced features

 Plane-Lok, Grade Match and Axis Alignment ensure accuracy and fast setup.





Wireless remotes included standard

required.

PIPE LASERS

DG511/DG711

range

Largest self-leveling

Stands up to the demanding underground

conditions. Proven rugged dependability.

OPTICAL INSTRUMENTS

DET-2 / ALXX-A/M Series **Digital Electronic Theodolite**

- 2 second accuracy for all construction applications.
- Dual sided LCD with large easy to read characters.
- Rechargeable and alkaline battery packs included.

Spectra Precision Auto Levels

- 20. 24. 28 or 32 power magnification.
- Choice of air dampened or magnetic dampened.


LASER RECEIVERS

HR's, HL's, CR600 Traditional laser receivers

- HR150U, HR320.
- Ideal for general exterior and interior applications.
- Models with LED's and/or LCD's.







Rod clamps are standard on all receivers

Advanced features including radio comn





on X/Y axes.

- unknown grade between two points.

keypad anywhere on the job site.

Specialty receivers

Line generator

receiver

Machine or rod mounted - CR600.

Universal receivers detect red, infrared

and green beams - HL750U, HR150U.







GL722 Grade Match, PlaneLok and

Long range Radio Remote Control.

MACHINE RECEIVERS

LR20. LR30W. LR50W. LR60W

Increase machine and operator productivity

- Check grade from the machine cab.
- Saves labor, time, and fuel.
- Use on backhoes, excavators, dozers, box blades, trenchers, and skid steer attachments.

All LR receivers feature

- Versatile 360 degree reception. Works with all types of rotating lasers.
- Multiple accuracy selections. Power options and long battery life.
- Ultra-bright LED's with green on-grade. LR30W-LR60W links wirelessly to the



accuracies





- 3 selectable
- and grading
- Built in blade tilt and and unique angle plumb indication



compensation

- Plumb indication

LR receivers accessories

LR60W
















the operator in the cab Works with LR30W, LR50W.



